	L #	Hits	Search Text	DBs	Time Stamp
1	L1	: u	viscosity same perhydropolysilazane	USPAT; US-PGP UB; EPO; JPO; DERWEN T; IBM_TD B	2002/12/10 14:36

(12) UK Patent Application (19) GB (11) 2 361 937 (13) A

(43) Date of A Publication 07.11.2001

(21) Application No 0025774.1

(22) Date of Filing 20.10.2000

(30) Priority Data

(31) 12023448 (32) 02.05.2000 (

(33) KR

(71) Applicant(s)

Samsung Electronics Company Limited (Incorporated in the Republic of Korea) 416 Maetan-dong, Paldal-gu, Suwon-city, Kyungki-do, Republic of Korea

(72) Inventor(s)

Jung Sik Choi Hong Ki Kim Dong Jun Lee Dae Won Kang Sang Mun Chon Jung Ho Lee

(74) Agent and/or Address for Service

Marks & Clerk 57-60 Lincoln's inn Fields, LONDON, WC2A 3LS, United Kingdom (51) INT CL7

C23C 18/12, C08G 77/62, H01L 21/3105 21/316

(52) UK CL (Edition S.)

C7F FHD FP905 FR850 FR901 FR902 FR903 FR909 FR913 FR916 FR919 F802 F809 U1S S1421 S2061

(56) Documents Cited

(58) Field of Search

UK CL (Edition S.) C3T TAD TAQ., C7F FHB FHD FHX., H1K KJAA KJAP INT CL⁷ C04B 41/45 41/50., C08G 77/62., C23C 18/02 18/12 18/14., H01L 21/3105 21/316 Online: WPI, EPODOC, JAPIO

(54) Abstract Title

Spin-on glass composition and method of forming silicon oxide layer

(57) A silicon oxide layer is formed by coating on a semiconductor substrate having a surface discontinuity, an SOG composition containing perhydropolysilazane having a compound of the formula -(SiH₂NH)_n- wherein n represents a positive integer, a weight average molecular weight within the range of about 4,000 to 8,000, and a molecular weight dispersion within the range of about 3.0 to 4.0, to form a planar SOG layer. The SOG layer is convened to a silicon oxide layer with a planar surface by curing the SOG layer. Solvent is present in the composition in an amount of 70-90% by weight.

GB 2361937 /